

直线曲线及转角表

2026年印茶镇百城村洞巴屯龙瓜产业路项目-支线

交点号	交点位置	交点间距 (m)	计算方位角 (° ’ ”)	曲线间 直线长 (m)	转角 (° ’ ”)	曲 线 要 素 值(m)						曲 线 主 点 位 置								备注
						切线长度	圆曲线半径	圆曲线长度	超高加宽 和段长度	曲线总长	外距	第一超高加 宽缓和段起 点	第一超高加 宽缓和段终 点	圆曲线起点	圆曲线中点	圆曲线终点	第二超高加 宽缓和段起 点	第二超高加 宽缓和段终 点		
						T	Ry	Ly	Lc1 Lc2											
JD0	K0+000.000																		起点坐标： X=409865.2290 Y=2592111.3190	
JD1	K0+010.396	10.396	187° 5’ 9”	3.876	右13° 31’ 15”	6.520	55.000	12.979	10.000 6.000	12.979	0.385	K0+000.000	K0+010.000	K0+003.876	K0+010.366	K0+016.855	K0+012.078	K0+018.078		
JD2	K0+023.151	12.816	173° 33’ 54”	2.445	左42° 7’ 15”	3.851	10.000	7.351	3.648	7.351	0.716			K0+019.301	K0+022.976	K0+026.652	K0+024.078	K0+027.726		
JD3	K0+047.349	24.548	215° 41’ 9”	2.149	右26° 6’ 28”	18.549	80.000	36.453	10.000 10.000	36.453	2.122	K0+027.726	K0+037.726	K0+028.801	K0+047.027	K0+065.254	K0+056.756	K0+066.756		
JD4	K0+080.762	34.057	189° 34’ 41”	3.005	右72° 40’ 8”	12.503	17.000	21.561	10.000 10.000	21.561	4.103	K0+066.756	K0+076.756	K0+068.259	K0+079.039	K0+089.820	K0+081.541	K0+091.541		
JD5	K0+101.884	24.567	116° 54’ 33”	3.442	左24° 19’ 40”	8.622	40.000	16.984	10.000 10.000	16.984	0.919	K0+091.541	K0+101.541	K0+093.262	K0+101.754	K0+110.246	K0+110.246	K0+120.246		
JD6	K0+136.401	34.777	141° 14’ 13”	22.256	右20° 5’ 56”	3.899	22.000	7.717	2.799	7.717	0.343	K0+132.502	K0+135.301	K0+132.502	K0+136.361	K0+140.219				
JD7	K0+155.548	19.227	121° 8’ 17”	8.164	左21° 21’ 16”	7.165	38.000	14.163	9.000 10.000	14.163	0.670	K0+144.301	K0+153.301	K0+148.383	K0+155.465	K0+162.546	K0+157.197	K0+167.197		
JD8	K0+183.441	28.060	142° 29’ 33”	9.303	右88° 1’ 20”	11.593	12.000	18.435	10.000 10.000	18.435	4.685	K0+167.197	K0+177.197	K0+171.849	K0+181.066	K0+190.284	K0+182.835	K0+192.835		
JD9	K0+208.409	29.718	54° 28’ 13”	5.103	左66° 8’ 14”	13.022	20.000	23.086	10.000 10.000	23.086	3.866	K0+192.835	K0+202.835	K0+195.387	K0+206.930	K0+218.473	K0+214.271	K0+224.271		
JD10	K0+238.891	33.440	120° 36’ 27”	11.595	右10° 5’ 1”	8.822	100.000	17.599	10.000 10.000	17.599	0.388	K0+224.271	K0+234.271	K0+230.069	K0+238.868	K0+247.668	K0+247.668	K0+257.668		
JD11	K0+296.150	57.305	110° 31’ 26”	43.533	左44° 49’ 52”	4.950	12.000	9.389	10.000 10.000	9.389	0.981	K0+281.201	K0+291.201	K0+291.201	K0+295.895	K0+300.590	K0+300.000	K0+310.000		
JD12	K0+310.000	14.360	155° 21’ 18”	9.410																

编制：

复核：